

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of the Claims:**

1. **(Currently Amended)** An orthotic device, comprising:

a base unit having an elongated support member, at least one support pad adjacently positioned on and attached to said support member, a fastener extending between said support member and said support pad, and an aperture in said support member capable of receiving a connector therein;

said base unit conforming substantially about a forearm of a user;

a metacarpal unit having a metacarpal internal pad ~~mounted onto and projecting from~~ positioned on and attached to an external casing and an attachment member between said external casing and said metacarpal internal pad; and

a hinge system connecting said base unit to said metacarpal unit, said hinge system having a shell with a shell interior pad positioned on said shell and a plurality of apertures in said shell each capable of accepting the connector therein.

2. **(Cancelled)**

3. **(Previously Amended)** The orthotic device as recited in claim 1, wherein said elongated support member has at least one recess formed therein allowing said fastener to access said support pad.

4. **(Previously Amended)** The orthotic device as recited in claim 1, wherein said elongated support member, said shell and said external casing are each made of a material selected from the group consisting of: epoxy matrix carbon fiber, moldable carbon fiber, Kevlar composite material, plastic and thermoplastic material.

5. **(Previously Amended)** The orthotic device as recited in claim 1, wherein said at least one support pad, said metacarpal interior pad and said shell internal pad being made of a material selected from the group consisting of: open cell foam, closed cell foam, cotton, a viscoelastic polymer-gel or air filled member.

6-8. **(Cancelled)**

9. **(Currently Amended)** The orthotic device as recited in claim 1, ~~where~~ wherein said support pad is detachably affixed on said support member, where said internal pad is removably attached on said external casing, and where said interior pad is detachably fastened on said exterior shell.

10. **(Currently Amended)** The orthotic device as recited in claim 1, wherein said metacarpal unit swivels in a lateral fashion ~~in relation~~ due to said hinge system.

11. **(Currently Amended)** The orthotic device as recited in claim 1, wherein said hinge system is capable of moving up to a 45° angle in an upward ~~vertical~~ extension fashion with respect to the base unit.

12. **(Currently Amended)** The orthotic device as recited in claim 1, wherein said hinge system is capable of moving at up to 150° angle in a downward, flexing ~~motion~~ fashion with respect to the base unit.

13. **(Original)** The orthotic device as recited in claim 1, wherein said elongated support member and said shell each have at least one stop formed thereon, wherein each of said stop abuts one another to limit extension, flexion and ulnar-radial deviation.

14-15. **(Cancelled)**

16. **(Currently Amended)** An orthotic device for rehabilitation of a user's wrist, comprising:

a base unit having an elongated support member and conforming substantially to a forearm of the user, a support pad at least partially on said

support member, a fastener extending between said support member and said support pad, and an aperture in said support member capable of receiving a connector therein[[:]], said elongated support member having at least one recess formed therein allowing said fastener to access said support pad;

a metacarpal unit having a metacarpal pad at least partially on an external casing and an attachment member between said external casing and said metacarpal pad; and

a hinge system connecting said base unit to said metacarpal unit, said hinge system having a shell with a plurality of apertures in said shell each capable of accepting the connector therein.

17. **(Cancelled)**

18. **(Previously Presented)** The orthotic device as recited in claim 16, wherein said elongated support member, said shell and said casing are each made of a material selected from the group consisting of: epoxy matrix carbon fiber, moldable carbon fiber, Kevlar composite material, plastic and thermoplastic material.

19. **(Previously Presented)** The orthotic device as recited in claim 16, wherein said support pad and said metacarpal interior pad each being made of a material selected from the group consisting of: open cell foam, closed cell foam, cotton, a viscoelastic polymer-gel or air filled member.

20. **(Previously Presented)** The orthotic device as recited in claim 16, where said support pad is detachably affixed on said support member, and said metacarpal pad is removably attached on said external casing.

21. **(Previously Presented)** The orthotic device as recited in claim 16, wherein said metacarpal unit swivels in a lateral fashion in relation to said hinge system.

22. **(Previously Presented)** The orthotic device as recited in claim 1, wherein said elongated support member and said shell each have at least one stop thereon to limit extension.

23. **(Currently Amended)** An orthotic device, comprising:

a base unit having an elongated support member and a support pad at least partially on said support member, a fastener extending between said support member and said support pad, and a plurality of apertures in said support member each capable of receiving a connector therein;

a metacarpal unit having a metacarpal pad at least partially on an external casing and an attachment member between said external casing and said metacarpal pad; and

a hinge system connecting said base unit to said metacarpal unit, said hinge system having a shell and a plurality of apertures in said shell each

capable of accepting a corresponding connector therein, and said metacarpal unit swivels in a lateral fashion ~~in relation~~ due to said hinge system.

24. **(Previously Presented)** The orthotic device as recited in claim 23, where said support pad is detachably affixed on said support member, and said metacarpal pad is removably attached on said external casing.

25. **(Previously Presented)** The orthotic device as recited in claim 23, wherein said elongated support member and said shell each have at least one stop formed thereon to limit extension.

26. **(New)** The orthotic device as recited in claim 23, wherein said hinge system is capable of moving up to a 45° angle in an upward extension with respect to the base unit.

27. **(New)** An orthotic device, comprising:

a base unit having an elongated support member and a support pad at least partially on said support member, a fastener extending between said support member and said support pad, and a plurality of apertures in said support member each capable of receiving a connector therein;

wherein said support pad is detachably affixed on said support member, where said internal pad is removably attached on said external casing, and where said interior pad is detachably fastened on said exterior shell;

a metacarpal unit having a metacarpal pad at least partially on an external casing and an attachment member between said external casing and said metacarpal pad;

a hinge system connecting said base unit to said metacarpal unit, said hinge system having a shell and a plurality of apertures in said shell each capable of accepting a corresponding connector therein, and said metacarpal unit swivels in a lateral fashion in relation to said hinge system; and

said support pad is detachably affixed on said support member, where said internal pad is removably attached on said external casing, and where said interior pad is detachably fastened on said exterior shell.

28. **(New)** The orthotic device as recited in claim 27, wherein said hinge system is capable of moving up to a 45° angle in an upward extension fashion with respect to the base unit.

29. **(New)** The orthotic device as recited in claim 27, wherein said elongated support member and said shell each have at least one stop formed thereon, wherein each of said stop abuts one another to limit extension, flexion and ulnar-radial deviation.

30. **(New)** An orthotic device, comprising:

a base unit having an elongated support member, at least one support pad adjacently positioned on and attached to said support member, a fastener

extending between said support member and said support pad, and an aperture in said support member capable of receiving a connector therein;

a metacarpal unit having a metacarpal internal pad mounted onto and projecting from an external casing and an attachment member between said external casing and said metacarpal internal pad;

a hinge system connecting said base unit to said metacarpal unit, said hinge system having a shell with a shell interior pad positioned on said shell and a plurality of apertures in said shell each capable of accepting the connector therein; and

said metacarpal unit swivels in a lateral fashion due to said hinge system.

31. **(New)** The orthotic device as recited in claim 30, wherein said elongated support member and said shell each have at least one stop formed thereon, wherein each of said stop abuts one another to limit extension, flexion and ulnar-radial deviation.

32. **(New)** The orthotic device as recited in claim 30, wherein said hinge system is capable of moving up to a 45° angle in an upward extension fashion with respect to the base unit.

33. **(New)** The orthotic device as recited in claim 30, wherein said hinge system is capable of moving at up to 150° angle in a downward, flexing fashion with respect to the base unit.



34. **(New)** The orthotic device as recited in claim 30, wherein said elongated support member and said shell each have at least one stop thereon to limit extension.

35. **(New)** The orthotic device as recited in claim 30, where said support pad is detachably affixed on said support member, and said metacarpal pad is removably attached on said external casing.